



PC-Prime® 02

Ready to use water-based bitumen primer

PC-Prime® 02 is a Water based primer is formulated using bitumen dispersion in a solvent-free water base. Its neutral fragrance makes it especially suitable for indoor applications.

AREA OF APPLICATION

The PC-Prime® 02 is specifically formulated to prime surfaces before the installation of bitumen roofing and waterproofing materials. Its application is crucial to promote robust adhesion of bitumen-based waterproofing materials to porous, rough, and dusty surfaces.

PRODUCTS PROPERTIES

Physical Properties	Typical Value
Content of bitumen with emulsifier, %	25-40
Drying time at 20°C, h	≤1
Relative viscosity (nozzle diameter 4 mm), s	5-30
Softening temperature, °C	≥80
Consumption, l/m ²	0.25-0.35
Bucket volume, l	20

NOTE: Avoid contact with skin and eyes.

SHELF LIFE

24 months from production date, if stored in original sealed packaging, in areas protected from humidity and direct sun exposure



PERFORMANCE OF WORKS

The application of the PC-Prime® 02 can be achieved using a roller or various brush sizes. This user-friendly primer streamlines the application process and enhances overall performance. It is advised to apply the primer within a temperature range of +5°C to +40°C for optimal results.

More details on installation are given in the relevant manuals of pc-wc global fz llc .

STORAGE

The product should be stored in a dry place protected from direct sunlight at temperatures of +5°C.

PACKAGING INFORMATION

Metal euro buckets of 20 Ltr.



PC-WC GLOBAL FZ-LLC

Compass Building, Al Shohada Road Al-Hamra industrial Zone-FZ, Ras Al-Khaimah, UAE
 Email: info@pc-wc.com
 Phone +971542455817, www.pc-wc.com

TECHNICAL DATA SHEET UPDATED IN
 SEPTEMBER 2020
 TDS/PC-PRIME® 02/20

All technical data in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

The information, particularly the recommendations relating to the application and end-use of PC-WC products, are given in good faith based on PC-WC's current knowledge and experience of the products when properly stored, handled and applied under normal conditions by PC-WC recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or any other advice offered. The user must test the product's suitability for the intended application and purpose. PC-WC Global FZ-LLC reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Our technical assistance is at the disposal of the users. Consult the latest update of the technical data sheet on our website www.pc-wc.com