



# PC-Deccor® Putty 2

## Ready-to use mixed Interior Putty type Skimming Compound

PC-Deccor® Putty 2 is a versatile interior filler and board skimming compound ideal for a range of building surfaces such as sand/cement renders and gypsum boards. This product provides a refined and premium surface suitable for painting, offering easy and swift application. It is tailored for effective skim coating on both existing and fresh surfaces in preparation for painting.

### FEATURES

- This filler and board skimming compound provides exceptional versatility, suitable for application on a range of substrates.
- Featuring low Volatile Organic Compounds (VOC), it enhances human health and prioritizes environmental sustainability.
- Its extensive coverage capacity allows for the efficient coating of larger surface areas with minimal material consumption, resulting in cost-effective applications.



### AREAS OF USE

- Cementitious Materials
- Renders
- Gypsum Boards
- Spray Plasters
- Wood
- All Common Building Surfaces

### PC-DECCOR® PUTTY 2 IS PERFECT FOR

- Gypsum board skimming
- Repairing damages in plaster and paint work
- Touch up of interior surfaces
- Filling nail holes
- Around door profiles and skirtings

### HOW TO USE

- Initiate the process by applying a thin, uniform layer of filler.
  - Should a thicker application be necessary, consider applying multiple thin layers.
  - Ensure each layer is allowed to dry thoroughly before proceeding to the next.
  - Prior to painting, meticulously sand the final surface.
- For further instructions, consult the Technical Data Sheet.

### PRODUCTS PROPERTIES

Physical Properties	Typical Value
Dilution	With a small quantity of water if required
Coverage	0.5 -1.5 kg/m <sup>2</sup> depending on substrate conditions
Layer Thickness	Maximum thickness 2mm/layer
Specific Gravity	1.70
Colour	Off-white
Standard Compliance	ASTM C-475
Packaging	5 and 25 kg plastic pails, 25 kg plastic bags
Storage	12 months in original unopened containers



### PC-WC GLOBAL FZ-LLC

Compass Building, Al Shohada Road Al-Hamra Industrial Zone-FZ, Ras Al-Khaimah, UAE  
 Email : info@pc-wc.com  
 Phone +971542455817 , www.pc-wc.com



TECHNICAL DATA SHEET UPDATED IN SEPTEMBER 2020  
 TDS/PC-DECCOR®PUTTY 2 /20

All technical data in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

The information, particularly the recommendations relating to the application and end-use of PC-WC products, are given in good faith based on PC-WC's current knowledge and experience of the products when properly stored, handled and applied under normal conditions by PC-WC recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or any other advice offered. The user must test the product's suitability for the intended application and purpose. PC-WC Global FZ-LLC reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Our technical assistance is at the disposal of the users. Consult the latest update of the technical data sheet on our website [www.pc-wc.com](http://www.pc-wc.com)