



PC-Deccotone® Stone

PC-Deccotone® Stone, an exterior acrylic render, epitomizes these traits through its outstanding weather-resistant properties. By incorporating natural stone aggregates and employing a spray application technique, **PC-Deccotone® Stone** successfully replicates the appearance of 'Hammer Finished Granite'. This stone-like coating is increasingly favored for its environmentally conscious practices, utilizing recycled materials that would otherwise go to waste.

FEATURES & BENEFITS

- Excellent weather and UV resistance.
- Outstanding flexibility.
- Excellent impact and abrasion resistance.
- Rapid drying properties in both low and high temperatures.
- Vapour permeable allowing substrate to breathe.
- (ASTM E96)
- Water based and environmentally friendly.

USES & APPLICATION

- Primarily intended for exterior applications, this product is frequently utilized internally by designers.
- Applicable to a wide range of surfaces including concrete, cement rendering, lightweight concrete, cement fiberboards, Sprayplaster, gypsum dry walls, and chipboard.
- Specifically crafted to replicate the appearance of natural 'Hammer Finished Granite'.
- Widely employed in various settings such as government buildings, commercial complexes, educational institutions and more.
- Especially suitable for PC-WC Exterior Insulation and Finish Systems (EIFS).

TECHNICAL INFORMATION

Architectural Specification:

Prepare the substrate by removing any loose or crumbly material, filling in any gaps as necessary, and ensuring the surface is clean, dry, and stable.

New Work:

Apply a coat of **PC-Prime®PGM** using a roller and allow it to cure. Subsequently, apply a coat of **PC-Deccotone® Stone** undercoat with a roller and let it cure. Finally, spray apply **PC-Deccotone® Stone** to achieve a color and texture consistent with the approved architectural sample.

Redecoration:

Safeguard all adjacent areas that require protection from coverage. Address any cracks, chips, voids, or damages by applying an appropriate filler. Initiate the process by removing loose or peeling paint, along with any grease, dirt, or grime. Apply primer to any exposed surfaces as necessary, following standard procedures for new projects.

PRODUCTS PROPERTIES

Physical Properties	Typical Value
PC-Prime® PGM	0.15-0.2 kg/m ²
PC-Deccotone® Stone undercoat	0.2-0.3 kg/m ²
PC-Deccotone® Stone	2.5-3.5 kg/m ²

COLOUR: AVAILABLE IN A BESPOKE RANGE OF COLOURS.



PC-WC GLOBAL FZ-LLC

Compass Building, Al Shohada Road Al-Hamra Industrial Zone-FZ,
Ras Al-Khaimah, UAE
Email : info@pc-wc.com
Phone +971542455817 , www.pc-wc.com

TECHNICAL DATA SHEET UPDATED IN
SEPTEMBER 2020
TDS/PC-DECCOTONE®STONE/20

All technical data in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

The information, particularly the recommendations relating to the application and end-use of PC-WC products, are given in good faith based on PC-WC's current knowledge and experience of the products when properly stored, handled and applied under normal conditions by PC-WC recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or any other advice offered. The user must test the product's suitability for the intended application and purpose. PC-WC Global FZ-LLC reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Our technical assistance is at the disposal of the users. Consult the latest update of the technical data sheet on our [website www.pc-wc.com](http://www.pc-wc.com)